



Dimensions in mm

TSUBAKI CHAIN NO.	PITCH P		INNER WIDTH B1				ROLLER	
							S ROLLER D1	R ROLLER D4
RF2040	25.40	1"	7.95				7.92	15.88
RF2050	31.75	1 1/4"	9.53				10.16	19.05
RF2060	38.10	1 1/2"	12.70				11.91	22.23
RF2080	50.80	2"	15.88				15.88	28.58
RF2100	63.50	2 1/2"	19.05				19.05	39.69

Dimensions in mm

TSUBAKI CHAIN NO.	PIN						LINK PLATE		
	DIAMETER D2	LENGTH L1	LENGTH L2	LENGTH L3	LENGTH L4	LENGTH L	THICKNESS T	HEIGHT H	
RF2040	3.97	8.25	9.95	9.50	16.75	18.20	1.50	12.00	
RF2050	5.09	10.30	12.00	11.90	21.00	22.60	2.00	15.00	
RF2060	5.96	14.55	16.55	14.30	27.45	31.50	3.20	17.20	
RF2080	7.94	18.30	20.90	19.10	35.50	39.90	4.00	23.00	
RF2100	9.54	21.80	24.50	23.80	43.40	47.50	4.80	28.60	

Dimensions in mm

TSUBAKI CHAIN NO.	ATTACHMENT DIMENSIONS												ATTACHMENT MASS		
	C	C1	C3	K	N	O	O1	O2	S	X	X2	XS	A SA KG/ATT.	K SK KG/ATT.	EXT. PIN KG/ATT.
RF2040	12.70	11.10	13.60	9.50	19.10	3.60	5.20	4.10	9.10	19.30	17.60	19.80	0.003	0.006	0.001
RF2050	15.90	14.30	15.90	11.90	23.80	5.20	6.80	5.10	11.10	24.20	22.00	24.60	0.006	0.012	0.002
RF2060	21.45	17.50	19.10	14.30	28.60	5.20	8.70	6.10	14.70	31.50	28.20	30.60	0.017	0.034	0.003
RF2080	27.80	22.20	25.40	19.10	38.10	6.80	10.30	8.10	19.10	40.70	36.60	40.50	0.032	0.064	0.007
RF2100	33.35	28.60	31.80	23.80	47.60	8.70	14.30	10.10	23.40	49.90	44.90	50.40	0.060	0.120	0.012

- Connecting links are clip type for sizes up to RF2060, cotter type for size RF2080 to RF2100; all GK-1 attachments are cotter type.
- R-Roller is not available with GK-1 attachment.
- Special attachments are available on request.
- The listed sizes are stock items, other sizes are available on request.
- Chain with S type roller is indicated as RF2040S.
- Chain with R type roller is indicated as RF2040R.