



Dimensions in mm

TSUBAKI CHAIN NO.	PITCH P		INNER WIDTH B1	ROLLER	
				S ROLLER D1	R ROLLER D4
RF2040-HP-SS	25.40	1"	7.95	7.92	15.88
RF2050-HP-SS	31.75	1 1/4"	9.53	10.16	19.05
RF2060-HP-SS	38.10	1 1/2"	12.70	11.91	22.23
RF2080-HP-SS	50.80	2"	15.88	15.88	28.58

Dimensions in mm

TSUBAKI CHAIN NO.	PIN					LINK PLATE		APPROX. MASS	
	DIAMETER D2	HOLLOW PIN D8	LENGTH L1	LENGTH L2	LENGTH L	THICKNESS T	HEIGHT H	S BUSH KG/M	R ROLLER KG/M
RF2040-HP-SS	5.68	4.00	8.00	9.50	19.10	1.50	12.00	0.46	0.82
RF2050-HP-SS	7.22	5.12	10.05	11.65	23.40	2.00	15.00	0.75	1.21
RF2060-HP-SS	8.38	5.99	12.55	14.25	28.70	2.40	17.20	1.38	2.06
RF2080-HP-SS	11.38	8.02	16.25	17.80	35.70	3.20	23.00	1.80	2.81

- Chain with S type bush is indicated as RF2040S-HP-SS.
- Chain with R type roller is indicated as RF2040R-HP-SS.